

Philips LCD monitor

V Line 18.5" / 47 cm

193V5LSB2

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Compact design and VESA mount allow your workspace flexibility. it's a great choice!

Vivid pictures every time

• LED technology for vivid colors

Great choice

- Compact design saves space
- Mercury Free eco-friendly display
- · VESA mount allows for flexibility



Highlights

brightness across the screen.

Mercury Free

disposal.

White LED's are solid state devices which light up to

full, consistent brightness faster saving startup time.

LED's are free from mercury content which allows

for eco-friendly recycling and disposal process. LED's

allow for better dimming control of LCD backlight,

resulting in super high contrast ratio. It also gives

superior color reproduction thanks to consistent

Philips monitors with LED backlighting are free of

substances, which affects humans and animals. This

Mercury content, one of the most toxic natural

reduces the environmental impact of the display

throughout its life-cycle, from manufacturing to

LED technology

Specifications

Picture/Display

- LCD panel type: TFT-LCD
- · Backlight type: W-LED system
- Panel Size: 18.5 inch / 47 cm
- Effective viewing area: 409.8 (H) x 230.4 (V)
- · Aspect ratio: 16:9
- Optimum resolution: 1366 x 768 @ 60 Hz
- Response time (typical): 5 ms
- Brightness: 200 cd/m²
- Contrast ratio (typical): 700:1
- Pixel pitch: 0.30x 0.30 mm
- Viewing angle: 90° (H) / 65° (V), @ C/R > 10
- Display colors: 16.7 M
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V)
- sRGB

Connectivity

- Signal Input: VGA (Analog)
- Sync Input: Separate Sync

Convenience

- User convenience: Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukranian
- Other convenience: Kensington lock, VESA mount (100×100mm)
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 7, Windows 8

• Tilt: -3/10 degree

Power

- On mode: 8.76 W (typ.) (EnergyStar test method)
- · Energy Label Class: E
- Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)









- · Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: Built-in, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): $437 \times 338 \times 170 \text{ mm}$
- Product without stand (mm): 437 x 273 x 48 mm
- Packaging in mm (WxHxD): 481 x 350 x 103 mm

Weight

- Product with stand (kg): 2.15 kg
- Product without stand (kg): 1.94 kg
- Product with packaging (kg): 3.00 kg

Operating conditions

- \bullet Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 30,000 hour(s)

Sustainability

- · Environmental and energy: RoHS, Mercury Free
- \bullet Recyclable packaging material: 100 %

Compliance and standards

· Regulatory Approvals: BSMI, CE Mark, cETLus, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ ISO9241-307, WEEE

Cabinet

- Color: Black
- Finish: Hairline (front bezel) / Texture (rear cover)

What's in the box?

- · Monitor with stand
- · Cables: VGA, Power
- User Documentation





Issue date 2021-02-27

© 2021 Koninklijke Philips N.V. All Rights reserved.

Version: 14.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 03124 EAN: 87 12581 68816 5

www.philips.com